



UL Standard		B	C	D
额定电压/Rated Voltage(V)	Current(A)	300/15	150/15	300/10
IEC 标准/IEC Standard:				
过压类别/Overvoltage Category/污染等级/Pollution Degree		III/3	III/2	II/2
额定电压/电压(Rated Voltage(V)/Current(A))		/	320/20	/
额定脉冲电压(RV)/Rate Impulse Voltage(KV)		/	/	/
拧紧扭矩/Torque Tightening(N·m/Lb·In)			M2.5: 0.5/4/3	
接线范围(导线和软线)/Wire Range(Liquid and flexible)(AWG/mm²)			28~12 / 0.2~2.5	
间距/Pitch(mm)/线数范围/Poles			5.08/N=02~24P	
引线长度/Shipping length(mm)			9~10	
使用温度范围/Operating temperature(°C)			-40~+105	
符合 RoHS 环保要求/Conform to RoHS			Yes	

ITEM	NAME OF PART	MATERIAL	NOTES
7	Screw2	Steel	M2.5/Zn Plated
6	Screw1	Steel	M2.5/Zn Plated
5	Cage	Steel	M2.5/Zn Plated
4	Block	Steel	Zn Plated
3	Clamp	Copper alloy	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

公差/General tolerances(mm)	
0	>3
2	>6
3	>10
6	>18
10	>30
18	>50
30	>80
50	>120
80	>180
120	>250
180	>315
250	>400
315	>500
400	>630
500	>800
630	>1000

表面/Finish	公差/Tolerance
0.1/10	±Z

MATERIAL:	SURFACE:
MAT NO.:	
STATUS:	
APPD:	
CHKD:	
DRT:	
NAME:	
DRAWING NO.:	
SIZE: A4	SCALE:
TYPE:	SHEET
	REV
	1/1


宁波三安电子科技有限公司
 Sanan Electrical Technology Co. Ltd

ZESAKCM-5.08-XXP-1Y-00A(H)